

THE MOST SUSTAINABLE AND ENVIRONMENT FRIENDLY PROCESS FOR THE PRODUCTION OF RUBBER COATING PLATES USING "ZEROSOLVENT TECHNOLOGY"

***Polyester backed, bi-directional
and strippable plates
Very regular microground
and polished surface***

***Superior quality of compressible layer
Superior varnish lay-down achieving
incredibly high gloss level
No ink build up - ink trapping***

***Long lasting plates with excellent re-use rates
compatible with cad and manual cutting
Essential and high-tech construction for
superior stability, varnish transfer and easy stripping***

100% Solvent free

***New generation of coating
plates for all sheetfed applications***



***Innovation
and tradition***

Excellent varnishing quality with UV varnish
Highly resistance to delamination even with aggressive UV varnish

TECHNICAL DATA

	AcocoatUV Spectra115	AcocoatUV Spectra135	AcocoatUV Spectra195
Colour	Orange	Orange	Orange
Bi-directional	Yes	Yes	Yes
Carrier	Polyester	Polyester	Polyester
Compressible layer	No	No	Yes
Nominal Thickness	1,15 mm	1,35 mm	1,95 mm
Thickness range	1,13 ÷ 1,17 mm	1,33 ÷ 1,37 mm	1,93 ÷ 1,97 mm
Thick. of carrier	0,35	0,35	0,35
Thick. of compressible layer mm	-	-	0,60
Coating compatibility	UV	UV	UV
Roughness (Ra:µm)	0,7 ÷ 0,9	0,7 ÷ 0,9	0,7 ÷ 0,9
Stripping depth mm	0,80	1,00	1,00

CROSS SECTION

