



Diesel Generator

230V - 50Hz & 110V - 60Hz

GDG 9500EC & GDG 10500EC



Features and Benefits

- Half Century Experience in Generator Manufacturing
- Gasoline Engines with Advanced Technology and Quality
- · Alternators with Advanced Technology and Quality
- Easy to Carry
- High Quality and Reliable Technology
- Compact Design and Silent
- Suitable for Heavy-Duty
- Durable
- Wide Range of Affordable Spare Parts

- Low Noise Level
- Low Exhaust Emission
- Low Operating Cost
- Low Fuel Consumption
- Low Oil Consumption
- Light Weight
- Big Size Fuel Tank
- First Class Product Support
- Global Technical Service and Maintenance Support

Generator General Information														
Generator Model	Frequency Hz	Voltage	Power Factor Speed		Diesel Engine			Alternator		Type of Operation	Generator Output			
	112	'	CosQ	ipiii	Brand	Model	Series	Brand	Model	Series	Operation	kVA	kW	Α
GDG 9500EC	50	230	0,8	3000	GENPOWER 192	192	FE	GENPOWER	GNP	1	Maximum	8,8	7,0	38,3
											Rated	7,5	6,0	32,6
GDG 10500EC	60	110	0,8	3600		FE	GENFOWER	UN		Maximum	9,7	7,8	88,2	
	00	110									Rated	8,5	6,8	77,3
We also make productions: 220, 230, 240, 110/220, 115/230, 120/240, 220/380, 230/400, 240/415V and 50Hz or 60Hz														

Diesel Engine General Data

- Single Cylinder, with Injector and Fuel Pump
- Vertical Type
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled Direct Injection
- 4 StrokeBig Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start

Alternator

- Synchron Alternator
- Single Phase 230V / 110V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class
- IP 23 Protection Class
- Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR

Control Panel

• 1 pcs 12V DC Output

• 1 pcs Circuit Breaker

• 1 pcs Digital Panel

• 1 pcs ATS Socket

1 pcs Oil Lamp1 pcs Grounding Terminal

• %10-15 Total Harmonic (THD)

• 2 pcs 16A Schuko witp Cap

Equipment and Features

- Sound Proof Canopy (70-75 dBA)
- Robotic Painting with Electrostatic Powder Paint
- Heavy Duty Type Wheels and Handle
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal

Dimensions

Width

Length

Low Oil Level Alarm and Protection

Diesel Engine Technical Data

3		
Brand		Genpower
Model		GDE 192FE
Speed	rpm	3000 / 3600
Displacement	cm ³	499
Number of Cylinders		1
Bore x Stroke	mm	92 x 75

Net (with Box)- mm

Net (with Box)- mm

Cooling System		Air Cooled
Starting System		12V Electric Start
Running Time- %50 loading	Hour	22
Fuel		Diesel
Oil Capacity	It	1,65
Fuel Tank Capacity	It	30

Net (with Box)- mm

Net (with Box)- Kgr

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





Height

550 (565)

935 (945)

Factory Address
ASO II. Industrial Zone
2010 Street No: 18

850 (860)

177 (180)

2010 Street No: 18 06909 Temelli-Sincan/Ankara, Turkey Tel/ Fax: +90(312) 641 32 22 - 641 32 23 genpower@genpower.com.tr www.genpower.com.tr