

THE MOST SUSTAINABLE AND ENVIRONMENT FRIENDLY PROCESS FOR THE PRODUCTION OF RUBBER COATING PLATES USING "ZEROSOLVENT TECHNOLOGY"

***Polyester backed, bi-directional
and strippable plates
Very regular microground
and polished surface***

***Superior quality of compressible layer
Superior varnish lay-down achieving
incredibly high gloss level
No ink build up - ink trapping***

***Long lasting plates with excellent re-use rates
compatible with cad and manual cutting
Essential and high-tech construction for
superior stability, varnish transfer and easy stripping***

100% Solvent free

***New generation of coating
plates for all sheetfed applications***



***Innovation
and tradition***

New series of special *single face compressible* coating plates with improved varnishing characteristics

TECHNICAL DATA

	Acosupercoat 115	Acosupercoat 135	Acosupercoat 195
Colour	Patina Green	Patina Green	Patina Green
Bi-directional	Yes	Yes	Yes
Carrier	Polyester	Polyester	Polyester
Compressible layer	Yes	Yes	Yes
Nominal Thickness	1,15 mm	1,35 mm	1,95 mm
Thickness range	1,13 ÷ 1,17 mm	1,33 ÷ 1,37 mm	1,93 ÷ 1,97 mm
Thick. of carrier	0,35	0,35	0,35
Coating compatibility	Aqueous+UV	Aqueous+UV	Aqueous+UV
Roughness (Ra:µm)	0,4 ÷ 0,6	0,4 ÷ 0,6	0,4 ÷ 0,6
Stripping depth mm	0,8	1,00	1,60

CROSS SECTION

