

www.artec3d.com

KEY SPECS

Power consumption

Supported OS

Computer requirements

Minimum computer requirements

Range	Up to 110 m	Range noise, 90% reflectivity	0.12 mm @ 15 m
Ranging error	<0.70 mm @ 15 m	Range noise, 10% reflectivity	0.30 mm @ 15 m
Angular accuracy	25 arcseconds	Color	Two fully integrated 5 megapixel cameras
Hassle-free export into a wide range of formats:	Mesh: OBJ, PLY, WRL, STL, ACCAD: STEP, IGES, X_T Measi		oint cloud: BTX, PTX, XYZ

SYSTEM SPECIFICATIONS

Scanner type	Phase shift, hemispherical scanner with $360^{\circ} \times 270^{\circ}$ FOV
Distance measurement method	Phase-shift
Laser wavelength	1550 nm
Laser type	Continuous wave
Laser class: (IEC EN60825-1:2007)	Class 1
Internal coordinate representation unit	0.001 mm
Angular position data	
Beam diameter at aperture	3 mm
Beam diameter at aperture Internal angular representation unit (vertical/horizontal)	3 mm 1 arcsec
·	
Internal angular representation unit (vertical/horizontal)	
Internal angular representation unit (vertical/horizontal) Scan density control: software selectable	1 arcsec
Internal angular representation unit (vertical/horizontal) Scan density control: software selectable Min. vertical point density	1 arcsec 20 points/degree
Internal angular representation unit (vertical/horizontal) Scan density control: software selectable Min. vertical point density Min. horizontal point density	1 arcsec 20 points/degree 20 points/degree
Internal angular representation unit (vertical/horizontal) Scan density control: software selectable Min. vertical point density Min. horizontal point density Max vertical point density	1 arcsec 20 points/degree 20 points/degree 80 points/degree
Internal angular representation unit (vertical/horizontal) Scan density control: software selectable Min. vertical point density Min. horizontal point density Max vertical point density Max horizontal point density	1 arcsec 20 points/degree 20 points/degree 80 points/degree

30 W

Windows 7, 8 or 10 - x64

Intel Core i5, i7 or i9, 32GB RAM, GPU with 2 GB VRAM





ULTRA-HIGH PRECISION, FAST LASER SCANNER

CLEANEST 3D DATA
CAPTURE FOR MINIMUM
PROCESSING TIME

IDEAL FOR CONSTRUCTION, INSPECTION AND PRODUCT DESIGN

The fastest, most accurate laser scanner for capturing large objects such as wind turbines, ship propellers, airplanes and buildings. Producing 3D data of the highest quality, Artec Ray scans with submillimeter distance accuracy and best in class angular accuracy.

Furthermore, data capture is cleaner than that from any other 3D scanner of this type, with noise levels at an absolute minimum. This speeds up data processing significantly, making it a hassle free job.

APPLICATIONS



REVERSE ENGINEERING



INSPECTION CONSTRUCTION (BIM)



PRODUCT DESIGN



FORENSICS



NSICS HERITAGE
PRESERVATION

RAY-002-12/2020-EN-NOP



www.artec3d.com



EASY 3D SCANNING, HIGH PRECISION RESULTS

SCANNING WITH ARTEC RAY IS EASY

Just place it on a tripod in front of your object and press the button! Portable and compact, you can set it up indoors or outdoors, without need for a power source, since the internal battery will last you for up to 4 hours.

SOFTWARE

Scan and process directly in the powerful Artec Studio, then seamlessly **export to Geomagic Design X**.






THE FULL 3D SCANNING PACKAGE









Pair it with an Artec handheld scanner, such as Leo, Eva or Space Spider, to scan difficult to reach areas, e.g. the interior of a car, or to easily add intricate detail to a large-scale 3D model. Armed with Artec Ray and an Artec handheld scanner, there will be virtually no limits to what you can capture in 3D.

SPECIFICATIONS	High Quality mode	High Sensitivity mode
Recommended work range	1-50 m	1-110 m
Ranging error	<0.70 mm @ 15 m	<0.90 mm @ 15 m
Angular accuracy	25 arcsecs	25 arcsecs
Range noise, 90% reflectivity	0.12 mm @ 15 m	0.25mm @ 15m
Range noise, 10% reflectivity	0.30 mm @ 15 m	0.70 mm @ 15 m
Speed	208,000	pts/sec
Full volume scan time	122,000 pts/sec	
Scanning modes	Autonomou	s or via USB
Color	Two fully integrated 5	megapixel cameras

FIELD-OF-VIEW PER SCAN

Horizontal (maximum)	360°
Vertical (maximum)	270°

PHYSICAL DIMENSIONS AND WEIGHT

Weight with battery	5.74kg
Dimensions L × H × W	287 mm × 200 mm × 118 mm

